



DOMESTIC HOT WATER TANKS WITH TWO DOUBLE HIGH
OUTPUT HEAT EXCHANGERS

EV 2X9 2X14 S2 800 99
HP DN18

SAP код	306389
Capacity	741 L
Net weight	308 kg
Insulation	100 mm
Heat exchanger surface S1	2.50 m ²
Heat exchanger surface S2	3.80 m ²
Heat exchanger capacity S1	14.40 L
Heat exchanger capacity S2	22.70 L
Heat losses ΔT 45K	128 W



Energy class	C
Maximum operational temperature	95 °C
Maximum operational temperature of the heat exchanger	110 °C
Rated pressure of the water tank	8 bar
Rated pressure of the heat exchanger	6 bar
Diameter	990 mm



Information

EV 2x9 2x14 S2 800 99 HP DN18

- **DOUBLE HIGH OUTPUT HEAT EXCHANGER** increases the efficiency of low-temperature heat sources.
- Decreased hydraulic resistance (pressure drop) of the heat exchanger with a larger diameter of the inlet and outlet on G1 1/2. (160 L model with inlets/outlets on G1).
- Heat exchangers with large surfaces for connection to heat pump or condensing gas boiler systems.
- Suitable to operation with low temperature heat sources.
- High quality **ENAMEL COATING** with **TESY CrystalTech PRO** technology.
- **MAGNESIUM ANODES PROTECTION** of the inner tank surface for extended product life.
- Highly efficient **REMOVABLE EPS INSULATION** for models 800 L and 1000 L.

Serie information

EV 2x9 2x14 S2 800 99 HP DN18

The range includes models from from 200 L to 1000 L. **DOUBLE HIGH OUTPUT HEAT EXCHANGER** increases the efficiency of low-temperature heat sources.

*Product photos, displayed in this website, are with illustration purpose only.