

Aquarea T-CAP Hydraulic M Series outdoor units. Single phase / Three phase · R290

Natural refrigerant R290 with GWP 0,02.

Energy efficiency: A+++ in heating at 35 °C / Built-in flow meter.

Flexibility: Hydraulic connection between indoor and outdoor / Built-in magnetic water filter.

Comfort: Constant capacity down to -20 °C / Operating range down to -28 °C / 75 °C water temperature at -15 °C outside / 55 °C hot water even at -25 °C outside temperature / Low noise level.

Control: Optimised user interface and improved features (2 zone control, bivalent control).



* For All in One.

Combination table - Aquarea T-CAP Hydraulic M Series					Outdoor unit				
Indoor unit					Heating capacity				
	DHW tank	Backup heater capacity	Electrical anode		Single phase		Three phase		
					9,0 kW	12,0 kW	9,0 kW	12,0 kW	16,0 kW
					WH-WXG09ME5	WH-WXG12ME5	WH-WXG09ME8	WH-WXG12ME8	WH-WXG16ME8
Hydraulic All in One	120 L	3 kW	—	WH-ADC0916M3E51	✓	✓	—	—	—
	120 L	3 kW	✓	WH-ADC0916M3E5AN1	✓	✓	—	—	—
	185 L	3 kW	—	WH-ADC0916M3E52	✓	✓	—	—	—
	185 L	3 kW	✓	WH-ADC0916M3E5AN2	✓	✓	—	—	—
	185 L	6 kW	—	WH-ADC0916M6E52	✓	✓	—	—	—
	260 L	3 kW	—	WH-ADC0916M3E53	✓	✓	—	—	—
	260 L	3 kW	✓	WH-ADC0916M3E5AN3	✓	✓	—	—	—
	260 L	6 kW	—	WH-ADC0916M6E53	✓	✓	—	—	—
	120 L	9 kW	—	WH-ADC0916M9E81	—	—	✓	✓	✓
	120 L	9 kW	✓	WH-ADC0916M9E8AN1	—	—	✓	✓	✓
	185 L	9 kW	—	WH-ADC0316M9E82	✓	✓	✓	✓	✓
	185 L	9 kW	✓	WH-ADC0316M9E8AN2	✓	✓	✓	✓	✓
	260 L	9 kW	—	WH-ADC0316M9E83	✓	✓	✓	✓	✓
	260 L	9 kW	✓	WH-ADC0316M9E8AN3	✓	✓	✓	✓	✓
Hydraulic Bi-bloc	1ph	—	3 kW	—	WH-SDC0916M3E5	✓	—	—	—
	—	—	6 kW	—	WH-SDC0916M6E5	✓	—	—	—
	3ph	—	9 kW	—	WH-SDC0316M9E8	✓	✓	✓	✓
Control module	1ph	—	—	WH-CME5	✓	✓	—	—	—
	3ph	—	—	WH-CME8	✓	✓	✓	✓	✓
Remote controller with Wi-Fi adapter	—	—	—	CZ-RTW2TAW1C	✓	✓	✓	✓	✓

Combination table - Big Aquarea T-CAP Hydraulic M Series					Outdoor unit		
Indoor unit					Heating capacity		
					Three phase		
					20,0 kW	25,0 kW	30,0 kW
					WH-WXG20ME8	WH-WXG25ME8	WH-WXG30ME8
Control module	3ph	—	WH-CME8L	—	✓	✓	✓
Remote controller with Wi-Fi adapter	—	—	CZ-RTW2TAW1C	—	✓	✓	✓

Accessories	
CZ-RTW2TAW1C	Remote controller with Wi-Fi adapter (required for stand-alone outdoor units). M Series
CZ-RTW2	Optional remote controller for 2 zone control. M Series
CZ-NS6P	PCB for advanced functions. M Series All in One and Bi-bloc
CZ-NS7P	PCB for advanced functions. M Series control module
PAW-A2W-RTWIRED	Room thermostat
PAW-A2W-RTWIREDLESS	Wireless LCD room thermostat
PAW-A2W-AFVLV-112	1 antifreeze valve 1 1/2". It is required to order 2 valves per system. For 20, 25 and 30 kW
PAW-A2W-AFVLV-1	1 antifreeze valve. It is required to order 2 valves per system. For 9, 12 and 16 kW

Accessories	
PAW-TD20C1E5-1	Tank 200 L - Stainless steel
PAW-TD30C1E5-1	Tank 300 L - Stainless steel
PAW-TA20C1E5STD	Tank 200 L - Enamelled
PAW-TA30C1E5STD	Tank 300 L - Enamelled
PAW-3WYVLV-HW	3 way valve for DHW tanks
PAW-BTANK50L-2	Buffer tank 50 L
PAW-BTANK100L	Buffer tank 100 L
PAW-BTANKG200L	Buffer tank 200 L
PAW-BTANKG260L	Buffer tank 260 L



DHW A+: For All in One. INTERNET CONTROL: Wi-Fi adapter included.